

HYDRAULIC HOSE

2-Wire Braid Jack Hose

5220 SERIES

For 10,150 psi. static pressure only



APPLICATIONS: 10,150 psi. static jack line use. **DO NOT** use on any dynamic application

CONSTRUCTION:	Tube: Synthetic Rubber
	Cover: Oil, weather and abrasion resistant synthetic rubber, MSHA approved
	Reinforcement: Two wire braids of high tensile steel with protective coating

TEMPERATURE RANGE: -40°F (-40°C) to +212°F (+100°C)

COUPLINGS: 1220L Couplings - page 68

Part Number	Inside Diameter		Outside Diameter		Working Pressure		Burst Pressure		Minimum Bend Radius		Weight		Standard Pack	
	inch	mm	inch	mm	PSI	BAR	PSI	BAR	inch	mm	lbs./ft.	kg/m	feet	meter
5220-04	1/4	6.4	0.59	15.0	10150	700	20300	1400	3.9	100	0.24	0.35	500	152.4
5220-06	3/8	9.5	0.75	19.0	10150	700	20300	1400	5.1	130	0.34	0.51	500	152.4

We disclaim any liability for use of our products in applications other than which they are designed.

WARNING: This product can expose you to chemicals including carbon black, which is known to the State of California to cause cancer, birth defects or other reproductive harm. For more information visit www.P65WARNINGS.ca.gov